



WESTERN SCALE CO. LTD.

Western Scale Co. Ltd.
1670 Kingsway Ave.
Port Coquitlam, B.C.
Canada V3C 3Y9

Tel: 1.604.941.3474
Fax: 1.604.941.4020
Email: info@westernscale.ca
Web: www.westernscale.ca

M2000-A WEIGHT INDICATOR

Fast. Accurate. Versatile. Reliable.

The M2000 A-3 is a high performance, digital weight indicator, suitable for use in practically any industrial application.

FEATURES

- 3 Scale channels
- 2 Fully configurable serial ports
- FASTSTEP Filtering for remarkably fast, stable readings
- Extremely resistant to interference (static, EMI, RFI)
- Accommodates load cell SENSE lines
- Full keypad calibration to any test weight amount
- 4 Linearity points
- Password and Category 1 Audit Trail system
- Custom Weigh Ticket Editor
- Interactive Ticket Macros for Accumulation, Truck In/Out, Axle weighing, and more...
- Store up to 100 truck IDs and tare weights
- Over 20 selectable output strings
- Serial Command mode
- Time & Date
- 6 Remote Inputs (optional)
- 6 Setpoints (optional)
- 4-20 mA Output (optional)



* LSB Enclosure

SPECIFICATIONS

POWER REQUIREMENTS

- Input: 12 VDC 1 A. 120 VAC adapter included for most models.
- External AC adapter available for SL models.
- Consumption: 200 mA

EXCITATION

- 7.5 VDC. Up to 16 350 ohm or 32 700 ohm load cells

ANALOG INPUT RANGE

- Selectable: 0-9 mV; 0-19 mV; 0-39 mV; 0-79 mV

RESOLUTION

- 1,000,000 internal A/D counts
- Up to 100,000 displayed divisions

MEASUREMENT RATE

- 100 weight samples/second

ANALOG SIGNAL SENSITIVITY

- .3 μ V

COMMUNICATIONS

- 2 fully configurable, full duplex serial ports.
- Supports RS-232, RS-422, and optional RS-485 Multi-drop.
- Wireless Communication Module (Optional)

RFI PROTECTION

- Filtered Excitation, Signal, and Sense lines

SYSTEM LINEARITY

- 0.01% of Full Scale

KEYPAD

- Membrane keypad: 16 numeric & function keys.

DISPLAY

- 3/4" (19 mm) LED display.
- 6 digit (7 segments each)

OPERATING TEMPERATURE

- 14°F to 104°F (-10°C to 40°C)

APPROVALS

- NTEP Class III/IIIL (10,000): 00-076A1
- Measurement Canada Class III (10,000) / IIIHD (20,000): AM 5371

WARRANTY

- 2 year standard warranty